



# LZR®-WIDESCAN

MOTION, PRESENCE, & SAFETY SENSOR  
FOR INDUSTRIAL DOORS



## DESCRIPTION


BEA's **LZR®-WIDESCAN** is a LASER-based, Time-of-Flight sensor used for motion, safety and presence detection in a variety of industrial door applications. This highly-configurable solution offers the benefits of activation and safety, while reducing installation time.

This IP65 rated sensor creates a volumetric detection area by generating seven angled LASER curtains. It has the ability to detect objects based on direction, speed, object size and height.


The **LZR®-WIDESCAN** detection field operates independent of ground conditions, allowing for superior functionality in harsh environments.

Easily configure sensor settings with **LZR®-WIDESCAN** mobile app. The mobile app provides a complete view of sensor settings, from field configurations to immunity.

## APPLICATIONS




Dynamic Ground Conditions



Pedestrian Safety

## DIMENSIONS



**DISCLAIMER** Information is supplied upon the condition that the persons receiving it will make their own determination as to its suitability for their purposes prior to use. In no event will BEA be responsible for damages of any nature whatsoever resulting from the use of or reliance upon information from this document or the products to which the information refers. BEA has the right without liability to change descriptions and specifications at any time.

## TECHNICAL SPECIFICATIONS

### TECHNOLOGY / PERFORMANCE

<b>Technology</b>	LASER scanner, time-of-flight measurement (7 laser curtains)
<b>Detection mode</b>	motion, presence, height, and speed
<b>Max. detection field</b>	width: 1.2 x mounting height depth: 1.2 x mounting height adjustable, depending on user settings
<b>Thickness of first curtain</b>	1/4"
<b>Typ. mounting height</b>	6'6" – 32'
<b>Min. reflectivity factor</b>	> 2 % (of floor and object) (measured at max. 19'6" in safety field)
<b>Typ. min. object size</b>	6" at 19'6" (in proportion to object distance)
<b>Testbody</b>	27 1/2" x 11 3/4" x 7 3/4"

### ELECTRICAL

#### Emission characteristics

IR laser:	wavelength 905 nm; output power 0.10mW (CLASS 1)
Red visible laser:	wavelength 635 nm; output power 0.95mW (CLASS 2)

<b>Supply voltage</b>	12 – 24 VAC -10/+20% 12 – 30 VDC ±10% at sensor terminal
<b>Power consumption</b>	< 2.5 W (heating = OFF) < 10 W, max 15 W (heating = ECO or AUTO)
<b>Response time</b>	typ. 230 ms max. 800 ms (depending on immunity settings)
<b>Output</b>	2 solid-state relays (galvanic isolation, polarity free) 24 VAC / 30 VDC (max. switching voltage) 100 mA (max. switching current) - in switching mode: NO/NC - in frequency mode: pulsed signal (f= 100 Hz ±10%)  1 electro-mechanic relay (galvanic isolation, polarity free) 42 VAC/DC (max. switching voltage) 500 mA (max. switching current)
<b>Input</b>	30 VDC (max. switching voltage) low < 1 V high > 10 V (voltage threshold)
<b>Bluetooth communication</b>	operating bandwidth: 2402 – 2480 MHz max. transmitted power: 12 dBm

### PHYSICAL

<b>Dimensions</b>	7 3/4" (H) x 6" (W) x 4" (D) (approx.)
<b>Material / Color</b>	PC, ASA / Black
<b>Protection degree</b>	NEMA 4 / IP65
<b>Temperature range</b>	-22 – 140 °F
<b>Rotation angles on bracket</b>	45° to the right 15° to the left (both directions lockable)
<b>Tilt angles on bracket</b>	-10 – 5°
<b>LED signals</b>	2 tri-colored LED: output status / remote control response / error signals 1 blue LED: Bluetooth status

### COMPLIANCE

<b>Compliance</b>	EN 300 328 V2.2.2, EN 301 489-1 V2.2.2, EN 301 489-17 V3.2.0, EN 60825-1:2014, EN 62311:2008; CSA/UL62368-1
-------------------	-------------------------------------------------------------------------------------------------------------

