
GATE ARMS+
LIGHTED FOR SAFETY



ELEVATION
(GATE 90° ANGLE DOWN POSITION
- FOLDARM90-46 SHOWN)

ELEVATION
(GATE ARM FULLY EXTENDED, DOWN POSITION
- FOLDARM90-46 SHOWN)

SPECIFICATIONS
FOLDARM90-46: PREASSEMBLED 90-DEGREE ARTICULATING ARM,
ARTICULATING LED & WIRING HARNESS, DOT TAPE 1-SIDE, ARTICULATING ARM KIT,
FOR 4 FT FIRST SECTION + 6 FT SECOND SECTION (LED CUTTABLE) **NO INSTALL KIT INCLUDED
FOLDING ARM AVAILABLE IN 3 DIFFERENT LENGHTS; LED SINGLE-SIDED AND DOUBLE-SIDED AVAILABLE.
MATERIAL: ALUMINUM
LED STRIP: IP68-RATED

MODEL #	LENGTH	WEIGHT
FOLDARM90-46	10'	15 LBS
FOLDARM90-56	11'	18 LBS
FOLDARM90-66	12'	21 LBS

NOTES:
1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5413-011.

LED SAFETY LIGHT SYSTEM

LED FOLDING BARRIER GATE ARM 90

5413-011

REVISION DATE 16/04/2021

PROTECTED BY COPYRIGHT ©2021 CADDETAILS.COM LTD.