



**ELEVATION**  
 (GATE 180° ANGLE DOWN POSITION  
 - FOLDARM180-44 SHOWN)

**ELEVATION**  
 (GATE ARM FULLY EXTENDED, DOWN POSITION  
 - FOLDARM180-44 SHOWN)

**SPECIFICATIONS**

**FOLDARM180-44:** PREASSEMBLED 180-DEGREE ARTICULATING 3" ALUMINUM BARRIER ARM, ARTICULATING LED & WIRING HARNESS, DOT TAPE 1-SIDE, ARTICULATING ARM KIT, FOR 4 FT FIRST SECTION (HEIGHT REDUCIBLE IN 1/2" INCREMENTS TO 3 FT) + 8 FT SECOND SECTION (CUTTABLE) \*\*NO INSTALL KIT INCLUDED (REQUIRED)  
 FOLDING ARM AVAILABLE IN 3 DIFFERENT LENGTHS; LED SINGLE-SIDED AND DOUBLE-SIDED AVAILABLE.

**MATERIAL:** ALUMINUM  
**LED STRIP:** IP68-RATED

MODEL #	LENGTH	WEIGHT
FOLDARM180-44	8'	15 LBS
FOLDARM180-55	10'	18 LBS
FOLDARM180-66	12'	21 LBS

**NOTES:**

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT [www.CADdetails.com/info](http://www.CADdetails.com/info) AND ENTER REFERENCE NUMBER 5413-014.

