

XL-CP74A36x

Part No: various

ExpertSystem XL

Safety edge / Contact profile

This datasheet provides technical data about single parts of the ExpertSystem XL safety edge family. Safety edges (also called sensors) are part of pressure-sensitive edge systems according to EN ISO 13856-2. A pressure-sensitive edge system consists of a safety edge and a control unit and its intended use is for pressure-sensitive protection systems.

Contact profile data

Designation / Art. No.	XL-CP74A / 389109			
Dimensions in mm (Tolerances acc. to DIN ISO 3302-1 tl. E2)	H 74 x W 43			
Contact profile material	EPDM, non-conductive, black			
Hardness	70 Shore A (+/- 5)			
Switching contact material	EPDM, conductive			
Delivery length	max. 25 m			
Weight per meter	0.89 kg/m			

Mounting profiles data

Designation	XL-AP36	XL-AP3620	XL-AP36Q	XL-AP3620Q
Art. No.	402163	409585	412006	412008
Material / Finish	Al / nature	Al / anod. black	Al / nature	Al / anod. black
Weight per meter	0.36 kg/m	0.45 kg/m	0.33 kg/m	0.42 kg/m
Delivery length	max. 6.1 m			

Safety edge data

Designation / Art. No.	XL-CP74A36x / various, see brochure			
Single sensor, length (min. / max.)	0.3 m / 20 m			
Cable length, max.	40 m			
Combined single sensors: max. number / sensor length in total / cable length in total	4 sensors / 20 m / 40 m			
Mounting orientations	All orientations			
Effective sensing surface (Figure A)	X = 34 mm / Z = 40 mm $\alpha = 150^\circ$ / L = sensor length			
Actuating distance / Pre-travel (A / 200mm/s)*	< 4 mm			
Actuating force (A / 200mm/s)*	< 45 N			
Overtravel at 250 N (B1)*	> 41 mm			
Overtravel at 400 N (B2)*	> 42 mm			
Total travel at 600 N (C)*	> 48 mm			
Operating temperature	-20°C to 60°C			
Switching cycles	> 10'000			
Degree of protection	IP67			
Max. voltage	24 V ACDC			
Continuous current load at max. voltage	10 mA			
Actuation resistance (typical / max.)	50 - 150 Ohm / 500 Ohm			
Standards	EN ISO 13856-2 / EN 12978			
EC type examination certificate No.	E 7194 (Suva)			

* Acc. to EN ISO 13856-2; Test piece Ø 80 mm; Test location c3; Test speed (A) 200 mm/s; Temp. 20°C
The actuating force and the deformation travels depend on the response time of the used signal processing unit. If the integrated radio transmitter XRF-TI is used, the overtravel and total travel values are reduced by 8mm, where the XRF-TI is located.

