
Product Profile



Features

- Works with these Diablo Detectors: DSP-40, DSP-50, DSP-13, and AVI-40.
- Single relay SPDT (Form C) output per slot with a Common, Normally Open, and Normally Closed.
- Includes four self-adhesive mounts.
- Operates over a wide range of voltages, AC or DC.

RK-3R Detector Rack with Built-in Relays

Many vehicle detectors are designed to be plugged into a rack including some of the more popular Diablo Controls models. In those installations where a large rack is not available, Diablo Controls has designed a mini rack. The RK-3R is designed to accept up to three plug-in vehicle detectors on one side and accept the appropriate wires through the terminal block on the other. The entire mini rack is supported by four adhesive standoffs that attach anywhere in the cabinet.

This device is designed for detectors that have a solid state output, but need a single relay output.

Accepts Diablo Controls models DSP-13, AVI-40, DSP-40, and DSP-50.

SPECIFICATIONS

Operating Temperature:	-35°F to 165°F (-37°C to 74°C)
Operating Voltages:	10.5 volts to 30 volts AC or DC.
Output Ratings:	3 amps @ 125 volts
Physical Size:	5.00" (H) x 3.00" (W) x 0.736" (D)
T Trystear 5126.	127.00 mm (H) x 76.20 mm (W) x 18.69 mm (D)

12-pin terminal block pin out

-	-
Pins	Function
1	AC Line or DC + (10V to 30V)
2	AC Neutral or DC COM
3	Output 1 Normally Open (Closes for detect)
4	Output 1 Common
5	Output 1 Normally Closed (Opens for detect)
6	Output 2 Normally Open (Closes for detect)
7	Output 2 Common
8	Output 2 Normally Closed (Opens for detect)
9	Output 3 Normally Open (Closes for detect)
10	Output 3 Common
11	Output 3 Normally Closed (Opens for detect)
12	Logic Common

6-pin terminal block pin out

•	•
Pins	Function
1	Loop 1
2	Loop 1
3	Loop 2
4	Loop 2
5	Loop 3
6	Loop 3



(800) 878-7829 www.GateOpenerSafety.com

