USVD-4X



ULTRASONIC VEHICLE DETECTOR

The device uses ultrasonic technology to reliably detect the presence of a vehicle in a wide variety of drive-thru applications including parking, access control, car wash, banking and fast food. Unlike a vehicle loop detector configuration that requires the installation of a loop in the pavement, the USVD-4X may be simply mounted on a post or order box and aimed at the location of the vehicle when in position to perform a transaction or place an order. Also, unlike other technologies, the USVD-4X does not require any set up or functional adjustments, other than simply installing and aiming. The USVD-4X greatly reduces the cost associated with installation of vehicle detection capabilities compared to loop detectors for these types of applications. The USVD-4X requires 12-24 VDC/AC and provides two form "C" relay contacts that indicate vehicle presence, pulse on entry or pulse on exit. The detection head consists of 4 ultrasonic transducers that connect to the internal microprocessor-based control board. The USVD-4X "scans" the expected location for a vehicle and activates its output upon detection of a vehicle.





ULTRASONIC VEHICLE DETECTOR

- · Easy set-up
- Reduces cost
- Ultrasonic technology
- Streamlining operation
- Robust design
- Aux. relay, settings for pulse on entry, exit or both
- · Output delay option for 1, 2 and 4 seconds





TECHNICAL DATA

Operating Range1ft. – 5ft.Response Time2.0 secondsRelay Output Configuration2 SPDT (form C)Relay Context Pating14 @ 24//DC
Relay Output Configuration2 SPDT (form C)
Below Contract Poting 14 @ 241/DC
Relay Contact Rating 1A @ 24VDC
Power Indicator/No Vehicle Green LED
Object In Range Flashing Green LED on each input, continuous LED on DETECT
Supply Voltage 12-24 VDC/AC
Operating Current 60mA
Operating Temperature -40°C-+85°C (-40°F-+182°F)
Dimensions Weight 5.7"(145mm) x 3.6"(90mm) x 2.3"(57mm)
Housing 0.6 lbs. (275g) ABS NEMA 4X
Connection 10 position terminal block

ORDERING INFORMATION

USVD-4X Ultrasonic vehicle detector, includes cable grip

WARRANTY EMX INC. the product described herein for a period of 2 years under normal use and service from the date of sale to our customer. The product will be free from defects in material and workmanship. This warranty does not cover ordinary wear and tear, abuse, misuse, overloading, altered products, or damage caused by the purchaser from incorrect connections, or lightning damage. There is no warranty of merchantability. There are no warranties expressed, implied or any affirmation of fact or representation which extend beyond the description set forth herein. EMX Inc. sole responsibility and liability, and purchaser's exclusive remedy shall be limited to the repair or replacement at EMX's option of a part or parts not so conforming to the warranty. In no event shall EMX Inc. be liable for damages of any nature, including incidental or consequential damages, including but, not limited to any damages resulting from non-conformity defect in material or workmanship. Rev 3 12/06/2022

